



Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 N/O, 24 V DC, DC operation, Screw terminals

Part no. DILM15-10-EA(24VDC)
190038

General specifications

Product name	Eaton Moeller® series DILM contactor
Part no.	DILM15-10-EA(24VDC)
EAN	4015081880348
Product Length/Depth	75 millimetre
Product height	68 millimetre
Product width	45 millimetre
Product weight	0.296 kilogram
Compliances	CE RoHS conform CE Marked
Product Tradename	DILM
Product Type	Contactor
Product Sub Type	None
Countries	Turkey Slovakia Romania Poland Czech Republic

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])		
Rated control supply voltage AC 50 Hz	V	0 - 0
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	24 - 24
Voltage type for actuating		DC
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3
Type of electrical connection of main circuit		Screw connection
Operating voltage AC 50 Hz	V	24 - 690
Operating voltage AC 60 Hz	V	24 - 690
Rated operation current Ie at AC-1, 400 V	A	22
Rated operation current Ie at AC-3, 400 V	A	15.5
Rated operation power at AC-3, 400 V	kW	7.5
Rated operation current Ie at AC-4, 400 V	A	7
Rated operation power at AC-4, 400 V	kW	3
Rated operation power NEMA	kW	7.4
Number of auxiliary contacts as normally open contact		1
Number of auxiliary contacts as normally closed contact		0
Modular version		No
Width	mm	45
Height	mm	68
Depth	mm	75