



Contactor, 3 pole, 380 V 400 V 55 kW, RDC 24: 24 - 27 V DC, DC operation,
Screw terminals

Part no. **DILM115-EA(RDC24)**
189926

General specifications			
Product name			Eaton Moeller® series DILM contactor
Part no.			DILM115-EA(RDC24)
EAN			4015081879229
Product Length/Depth			160 millimetre
Product height			170 millimetre
Product width			90 millimetre
Product weight			2.25 kilogram
Compliances			CE CE Marked RoHS conform
Product Tradename			DILM
Product Type			Contactor
Product Sub Type			None
Countries			Poland Romania Czech Republic Slovakia Turkey

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecI@ss13-27-37-10-03 [AAB718020])			
Rated control supply voltage AC 50 Hz	V		0 - 0
Rated control supply voltage AC 60 Hz	V		0 - 0
Rated control supply voltage DC	V		24 - 27
Voltage type for actuating			DC
Number of normally closed contacts as main contact			0
Number of normally open contacts as main contact			3
Type of electrical connection of main circuit			Screw connection
Operating voltage AC 50 Hz	V		230 - 690
Operating voltage AC 60 Hz	V		230 - 690
Rated operation current Ie at AC-1, 400 V	A		160
Rated operation current Ie at AC-3, 400 V	A		115
Rated operation power at AC-3, 400 V	kW		55
Rated operation current Ie at AC-4, 400 V	A		55
Rated operation power at AC-4, 400 V	kW		28
Rated operation power NEMA	kW		74
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Modular version			No
Width	mm		90
Height	mm		170
Depth	mm		160