



Contactor, 3 pole, 380 V 400 V 15 kW, 1 NC, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals

Part no. DILM32-01-EA(230V50HZ,240V60HZ)  
190003

General specifications

Product name		Eaton Moeller® series DILM contactor
Part no.		DILM32-01-EA(230V50HZ,240V60HZ)
EAN		4015081879991
Product Length/Depth		97 millimetre
Product height		85 millimetre
Product width		45 millimetre
Product weight		0.428 kilogram
Compliances		RoHS conform CE
Product Tradename		DILM
Product Type		Contactor
Product Sub Type		None
Countries		Poland Slovakia Romania Turkey Czech Republic

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])		
Rated control supply voltage AC 50 Hz	V	230 - 230
Rated control supply voltage AC 60 Hz	V	240 - 240
Rated control supply voltage DC	V	0 - 0
Voltage type for actuating		AC
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3
Type of electrical connection of main circuit		Screw connection
Operating voltage AC 50 Hz	V	24 - 690
Operating voltage AC 60 Hz	V	24 - 690
Rated operation current Ie at AC-1, 400 V	A	45
Rated operation current Ie at AC-3, 400 V	A	32
Rated operation power at AC-3, 400 V	kW	15
Rated operation current Ie at AC-4, 400 V	A	15
Rated operation power at AC-4, 400 V	kW	7
Rated operation power NEMA	kW	14.9
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		1
Modular version		No
Width	mm	45
Height	mm	85
Depth	mm	97