



Main switch, P5, 125 A, flush mounting, 3 pole, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Part no. P5-125/EA/SVB
280898
EL Number 1417175
(Norway)

General specifications		
Product name		Eaton Moeller® series P5 Main switch
Part no.		P5-125/EA/SVB
EAN		4015082808983
Product Length/Depth		115 millimetre
Product height		150 millimetre
Product width		130 millimetre
Product weight		1.138 kilogram
Certifications		VDE 0660 UL UL Category Control No.: NLRV, NLRV7 UL File No.: E36332 CSA-C22.2 No. 14-05 CSA-C22.2 No. 94 IEC/EN 60947 IEC/EN 60947-3 UL 508 CSA Class No.: 3211-05 IEC/EN 60204 CSA CE CSA File No.: 223805
Product Tradename		P5
Product Type		Main switch
Product Sub Type		None
Catalog Notes		Rated Short-time Withstand Current (Icw) for a time of 1 second
Features & Functions		
Features		Version as maintenance-/service switch Version as main switch Version as emergency stop installation
Fitted with:		Red rotary handle and yellow locking ring
Functions		Emergency switching off function Interlockable
Locking facility		Lockable in the 0 (Off) position
Number of poles		3
General information		
Accessories		Auxiliary contact or neutral conductor fitted by user.
Degree of protection		NEMA 12
Degree of protection (front side)		IP65
Lifespan, mechanical		100,000 Operations
Mounting method		Flush mounting
Mounting position		As required
Operating frequency		50 Operations/h
Overvoltage category		III
Pollution degree		3
Rated impulse withstand voltage (Uimp)		8000 V AC
Safe isolation		440 V AC, Between the contacts, According to EN 61140
Safety parameter (EN ISO 13849-1)		B10d values as per EN ISO 13849-1, table C.1
Suitable for		Front mounting 4-hole Branch circuits, suitable as motor disconnect, (UL/CSA)
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		50 °C

Ambient operating temperature (enclosed) - min			-25 °C
Ambient operating temperature (enclosed) - max			40 °C
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacities			
Terminal capacity			1 x 95 mm ² , solid or stranded 2/0 AWG, flexible 1 x 70 mm ² , flexible with ferrules to DIN 46228 2 x 13 x 1.5 mm Number of segments x width x thickness, copper strip 1 x 13 x 3 mm Number of segments x width x thickness, copper strip 2 x 35 mm ² , solid or stranded 2 x 25 mm ² , flexible with ferrules to DIN 46228 3/0 AWG, solid or flexible conductor with ferrule
Screw size			5 mm AF, Hexagon socket-head spanner, Terminal screw
Tightening torque			14 Nm, Screw terminals 125 lb-in, Screw terminals
Electrical rating			
Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3)			800 A
Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)			750 A
Rated breaking capacity at 500 V (cos phi to IEC 60947-3)			650 A
Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)			340 A
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V			72 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V			66 A
Rated operational current (Ie) at AC-3, 500 V			58 A
Rated operational current (Ie) at AC-3, 660 V, 690 V			32 A
Rated operational current (Ie) at AC-21, 440 V			125 A
Rated operational current (Ie) at AC-23A, 230 V			96 A
Rated operational current (Ie) at AC-23A, 400 V, 415 V			80 A
Rated operational current (Ie) at AC-23A, 500 V			78 A
Rated operational current (Ie) at AC-23A, 690 V			39 A
Rated operational current (Ie) at DC-1, load-break switches I/r = 1 ms			125 A
Rated operational current (Ie) at DC-23A, 24 V			125 A
Rated operational current (Ie) at DC-23A, 48 V			125 A
Rated operational current (Ie) at DC-23A, 60 V			125 A
Rated operational current (Ie) at DC-23A, 120 V			40 A
Rated operational power at AC-3, 380/400 V, 50 Hz			37 kW
Rated operational power at AC-3, 415 V, 50 Hz			37 kW
Rated operational power at AC-3, 500 V, 50 Hz			45 kW
Rated operational power at AC-3, 690 V, 50 Hz			30 kW
Rated operational power at AC-23A, 220/230 V, 50 Hz			30 kW
Rated operational power at AC-23A, 400 V, 50 Hz			45 kW
Rated operational power at AC-23A, 500 V, 50 Hz			55 kW
Rated operational power at AC-23A, 690 V, 50 Hz			37 kW
Rated operational voltage (Ue) at AC - max			690 V
Rated uninterrupted current (Iu)			125 A
Uninterrupted current			Rated uninterrupted current Iu is specified for max. cross-section.
Short-circuit rating			
Rated conditional short-circuit current (Iq)			30 kA
Rated short-time withstand current (Icw)			2,5 kA, Contacts, 1 second 2.5 kA
Short-circuit current rating (basic rating)			350A Class RK1, max. Fuse, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA)
Short-circuit current rating (high fault)			300 A, Class J, max. Fuse, SCCR (UL/CSA) 65 kA, SCCR (UL/CSA)
Short-circuit protection rating			125 A gG/gL, Fuse, Contacts
Switching capacity			
Load rating			1.3 x I# (with intermittent operation class 12, 60 % duty factor) 2 x I# (with intermittent operation class 12, 25 % duty factor) 1.6 x I# (with intermittent operation class 12, 40 % duty factor)
Number of contacts in series at DC-23A, 24 V			3

Number of contacts in series at DC-23A, 48 V			3
Number of contacts in series at DC-23A, 60 V			3
Number of contacts in series at DC-23A, 120 V			3
Switching capacity (main contacts, general use)			150 A, Rated uninterrupted current max. (UL/CSA)
Switching capacity (auxiliary contacts, general use)			10A, IU, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)			A600 (UL/CSA)
Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3)			850 A
Voltage per contact pair in series			42 V
Motor rating			
Assigned motor power at 115/120 V, 60 Hz, 1-phase			7.5 HP
Assigned motor power at 115/120 V, 60 Hz, 3-phase			15 HP
Assigned motor power at 230/240 V, 60 Hz, 1-phase			20 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase			30 HP
Assigned motor power at 277 V, 60 Hz, 1-phase			20 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase			60 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase			60 HP
Contacts			
Control circuit reliability			1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
Number of auxiliary contacts (change-over contacts)			0
Number of auxiliary contacts (normally closed contacts)			0
Number of auxiliary contacts (normally open contacts)			0
Actuator			
Actuator color			Red
Actuator type			Door coupling rotary drive
Design verification			
Equipment heat dissipation, current-dependent Pvid			3.1 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			3.1 W
Rated operational current for specified heat dissipation (In)			125 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			UV resistance only in connection with protective shield.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Switch disconnecter (low voltage) (EC000216)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecI@ss13-27-37-14-03 [AKF060018])			
Version as main switch			Yes
Version as maintenance-/service switch			Yes
Version as safety switch			No
Version as emergency stop installation			Yes
Version as reversing switch			No
Number of switches			1
Max. rated operation voltage Ue AC		V	690
Rated operating voltage		V	690 - 690
Rated permanent current Iu		A	125
Rated permanent current at AC-23, 400 V		A	125
Rated permanent current at AC-21, 400 V		A	125
Rated operation power at AC-3, 400 V		kW	37
Rated short-time withstand current Icw		kA	2.5
Rated operation power at AC-23, 400 V		kW	45
Switching power at 400 V		kW	45
Conditioned rated short-circuit current Iq		kA	30
Number of poles			3
Number of auxiliary contacts as normally closed contact			0
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0
Motor drive optional			No
Motor drive integrated			No
Voltage release optional			No
Device construction			Built-in device fixed built-in technique
Suitable for floor mounting			No
Suitable for front mounting 4-hole			Yes
Suitable for front mounting centre			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Colour control element			Red
Type of control element			Door coupling rotary drive
Interlockable			Yes
Type of electrical connection of main circuit			Frame clamp
With pre-assembled cabling			No
Degree of protection (IP), front side			IP65
Degree of protection (NEMA)			12
Width		mm	130
Height		mm	150
Depth		mm	115
Width in number of modular spacings			