

DATASHEET - M22-LEDC-W



LED element, white, base fixing, 12-30VAC/DC

Part no. M22-LEDC-W
216560
EL Number 4355371
(Norway)

General specifications		
Product name		Eaton Moeller® series M22 Accessory LED
Part no.		M22-LEDC-W
EAN		4015082165604
Product Length/Depth		38 millimetre
Product height		10 millimetre
Product width		37 millimetre
Product weight		0.011 kilogram
Compliances		CE Marked
Certifications		UL CSA File No.: 012528 CE UL 508 IEC 60947-5 CSA-C22.2 No. 14-05 CSA Std. C22.2 No. 94-91 VDE UL Category Control No.: NKCR IEC 60947-5-1 EN 60947-5 CSA Class No.: 3211-03 IEC/EN 60947-5 CSA-C22.2 No. 94-91 CSA CSA Std. C22.2 No. 14-05 UL File No.: E29184
Product Tradename		M22
Product Type		Accessory
Product Sub Type		LED
Features & Functions		
Color		White
Fitted with:		Light source Diode
Light color		White
General information		
Degree of protection		IP20
Lifespan, electrical		100,000 h (at 25°C, according to EN60064)
Operating torque		0.8 N·m
Overvoltage category		III
Pollution degree		3
Rated impulse withstand voltage (Uimp)		6000 V AC
Voltage type		AC/DC
Ambient conditions, mechanical		
Mounting position		As required
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacities		
Terminal capacity (solid)		0.75 - 2.5 mm ²

Terminal capacity (stranded)			0.5 - 2.5 mm²
Electrical rating			
Power consumption			Max. 0.26 W
Rated insulation voltage (Ui)			500 V
Rated operational current (Ie) - min			5 mA
Rated operational current (Ie) - max			14 mA
Rated operational voltage (Ue) at AC - max			30 V
Rated operational voltage (Ue) at AC - min			12 V
Rated operational voltage (Ue) at DC - max			30 V
Rated operational voltage (Ue) at DC - min			12 V
Communication			
Connection to SmartWire-DT			No
Connection type			Base fixing
Contacts			
Force for positive opening - min			0 N
Design verification			
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			0.45 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Lamp holder block for control circuit devices (EC000204)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Bulb socket block for command and alarm devices (ecl@ss13-27-37-12-09 [AKF027019])			
Transformer integrated			No
With integrated voltage decreasing resistor			No
With light source			Yes
With integrated diode			Yes
Lamp holder			None
Rated voltage Ue at AC 50 Hz		V	12 - 30

Rated voltage Ue at AC 60 Hz	V	12 - 30
Rated voltage Ue at DC	V	12 - 30
Voltage type for actuating		AC/DC
Lamp type		LED
Connection type auxiliary circuit		Screw connection
Colour light source		White
Type of fastening		Floor fastening