

Specifications



Eaton 197211

Eaton Moeller® series EASY Control relays easyE4 with display (expandable, Ethernet), 12/24 V DC, 24 V AC, Inputs Digital: 8, of which can be used as analog: 4, screw terminal

General specifications

PRODUCT NAME	Eaton Moeller® series EASY Control relay
CATALOG NUMBER	197211
EAN	4015081939480
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.25 kg
COMPLIANCES	<p>Eaton supports the product until its end of life</p> <p>IEC 60068-2-30 IEC 60068-2-6 IEC/EN 61000-4-2 CSA-C22.2 No. 61010 CULus per UL 61010 EN 61010 IEC/EN 61000-6-3 IEC/EN 61131-2 IEC/EN 61000-6-2 EN 50178 IEC 60068-2-27 UL Listed UL Category Control No.: NRAQ, NRAQ7 UL File No.: E205091 DNV GL CE UL hazardous location class I UL hazardous location division 2 UL hazardous location group A (acetylene) UL hazardous location</p>
CERTIFICATIONS	



Powering Business Worldwide

	group B (hydrogen) UL hazardous location group C (ethylene) UL hazardous location group D (propane) UL hazardous location class I UL hazardous location division 2 UL hazardous location group A (acetylene) UL hazardous location group B (hydrogen) UL hazardous location group C (ethylene) UL hazardous location group D (propane)
CATALOG NOTES	Accuracy of the real-time clock depending on ambient air temperature - fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible
MODEL CODE	EASY-E4-UC-12RC1

Features & Functions	
FEATURES	Expandable Display indication of 6 lines x 16 characters Networkable (Ethernet)
FITTED WITH:	Display Real time clock Relay output Keypad Timer
INDICATION	LCD-display used as status indication of Digital inputs 24 V DC LCD-display used as status indication of Digital inputs 12 V DC

General	
DEGREE OF PROTECTION	IP20
DISPLAY TEMPERATURE - MIN	0 °C
DISPLAY TEMPERATURE - MAX	55 °C
DISPLAY TYPE	Monochrome
FREQUENCY COUNTER	Pulse shape: Square (digital inputs 24 V DC) Cable length: ≤ 20 m (screened, Digital inputs 24 V DC) Number: 4 (I1, I2, I3, I4 - Digital inputs 24 V DC) Pulse pause ratio: 1:1 (Digital inputs 24 V DC) Counter frequency: 5 kHz (Digital inputs 24 V DC)
INPUT FREQUENCY	50/60 Hz (Digital inputs, at 24 V DC)
INSULATION RESISTANCE	According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
LIFESPAN, ELECTRICAL	25,000 Operations (Filament bulb load at

	1000 W, 230/240 V AC) 25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, uncompensated) 25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, with upstream electrical device) 25,000 Operations (Filament bulb load at 500 W, 115/120 V AC) 25,000 Operations (Fluorescent lamp load 1 x 58 W at 230/240 V AC, conventional, compensated)
LIFESPAN, MECHANICAL	10,000,000 Operations
MOUNTING METHOD	Screw fixing using fixing brackets ZB4-101-GF1 (accessories) Front build in possible Rail mounting possible Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Wall mounting/direct mounting
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
PRODUCT CATEGORY	Control relays easyE4
PROTECTION	Miniature circuit-breaker B16 or slow-blow 8 A fuse, Protection of an output relay
PROTOCOL	TCP/IP MODBUS
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6 kV (contact-coil)
RESIDUAL RIPPLE	≤ 5 %
RESOLUTION	<ul style="list-style-type: none"> • 1 min (Range H:M) • 1 s (Range M:S) • 12 Bit (value 0 - 4095, Analog inputs) • 5 ms (Range S)
SOFTWARE	EASYSOFT-SWLIC/easySoft

Ambient conditions, mechanical

DROP AND TOPPLE	50 mm Drop height, Drop to IEC/EN 60068-2-31
HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	0.3 m
MOUNTING POSITION	Vertical Horizontal
SHOCK RESISTANCE	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	10 - 57 Hz, 0.15 mm constant amplitude According to IEC/EN 60068-2-6 57 - 150 Hz, 2 g constant acceleration

SWITCHING FREQUENCY	10 Hz, Relay outputs 2 Hz, Resistive load/lamp load, Relay outputs 0.5 Hz, Inductive load, Relay outputs
TYPE	easyE4 base device
USED WITH	easyE4
UTILIZATION CATEGORY	B 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes AC R 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes DC
VOLTAGE TYPE	AC/DC

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
ENVIRONMENTAL CONDITIONS	Clearance in air and creepage distances according to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201 Condensation: prevent with appropriate measures
RELATIVE HUMIDITY	5 - 95 % (IEC 60068-2-30, IEC 60068-2-78)

Electro magnetic compatibility

AIR DISCHARGE	8 kV
BURST IMPULSE	2 kV, Supply cable 2 kV, Signal cable According to IEC/EN 61000-4-4
CONTACT DISCHARGE	6 kV
ELECTROMAGNETIC FIELDS	10 V/m at 0.8 - 1.0 GHz (according to IEC EN 61000-4-3) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class B (EN 61000-6-3)
SURGE RATING	1 kV, Supply cables, symmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5, power pulses (Surge), EMC 2 kV, Supply cables, asymmetrical, power pulses (Surge), EMC
VOLTAGE DIPS	≤ 1 ms from rated voltage (12 V DC) 10 ms

Terminal capacities

TERMINAL CAPACITY	0.2 - 4 mm ² (AWG 22 - 12), solid 0.2 - 2.5 mm ² (22 - 12 AWG), flexible with ferrule
SCREWDRIVER SIZE	3.5 x 0.8 mm, Terminal screw
TIGHTENING TORQUE	0.6 Nm, Screw terminals

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)

8 A

POWER CONSUMPTION

3 W

RATED BREAKING CAPACITY

300000 Operations at AC-
15, 250 V AC, 3 A (600
Ops./h)
200000 Operations at DC-
13, 24 V DC, 1 A (500
Ops./h)

RATED INSULATION VOLTAGE (UI)

240 V

RATED OPERATIONAL VOLTAGE

Max. 300 V DC
12 V DC (digital inputs)
Max. 300 V AC
240 V AC
24 V AC (-15 %/+10 % -
power supply)
24 V DC (digital inputs)
12/24 V DC (-15 %/+ 20 % -
power supply)
10.2 - 28.8 V DC
24 V AC (digital inputs)
20.4 - 26.4 V AC

SUPPLY FREQUENCY

50/60 Hz (± 5%)

SUPPLY VOLTAGE AT AC, 50 HZ - MIN

20.4 VAC

SUPPLY VOLTAGE AT AC, 50 HZ - MAX

26.4 VAC

SUPPLY VOLTAGE AT DC - MIN

10.2 VDC

SUPPLY VOLTAGE AT DC - MAX

28.8 VDC

UNINTERRUPTED CURRENT

1 A DC, at R 300 (UL/CSA)
8 A DC, at 24 V DC
(UL/CSA)
5 A AC, max. thermal
continuous current $\cos \phi$
= 1 at B 300 (UL/CSA)
10 A AC, at 240 V AC
(UL/CSA)

Short-circuit rating

SHORT-CIRCUIT PROTECTION

≥ 1A (T), Fuse, Power
supply

Communication

CONNECTION TYPE

Screw terminal
Ethernet: RJ45 plug, 8-pole

DATA TRANSFER RATE

10/100 MBit/s

Cable

CABLE LENGTH

100 m, unscreened, Digital
inputs 24 V DC
100 m, unscreened, Digital
inputs 24 V AC

	≤ 30 m, screened, Analog inputs 100 m, unscreened, Digital inputs 12 V DC 40 m (max. per input), Digital inputs 24 V DC
CABLE TYPE	CAT5

Input/Output

ACCURACY

± 2 s/day, Real-time clock to inputs (± 0.2 hYear)
± 2 %, (I7, I8) ± 0.12 V, of actual value, within a single device (Analog Inputs)
± 1 %, Repetition accuracy of timing relays (of values)
± 3 %, of actual value, two easy devices (Analog Inputs)

CONVERSIONS

Each CPU cycle, Analog inputs

DELAY TIME

0.015 ms typ., Digital inputs 12 V DC (I1 - I8), Delay time from 1 to 0, Debounce OFF
0.015 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 1 to 0, Debounce OFF
0.015 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 0 to 1, Debounce OFF
20 ms typ., Digital inputs 12 V DC (I1 - I8), Delay time from 1 to 0, Debounce ON
20 ms typ., Digital inputs 12 V DC (I1 - I8), Delay time from 0 to 1, Debounce ON
20 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 0 to 1, Debounce ON
20 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 1 to 0, Debounce ON
0.015 ms typ., Digital inputs 12 V DC (I1 - I8), Delay time from 0 to 1, Debounce OFF

INCREMENTAL COUNTER

Number of counter inputs: 2 (I1 + I2, I3 + I4)
Value range: -2147483648 to +2147483647
Pulse shape: Square
Pulse pause ratio: 1:1
Signal offset: 90°
Counter frequency: ≤ 5 kHz

INCREMENTAL ENCODER

Cable length: ≤ 20 m (screened)

INPUT

Voltage (DC)

Safety

EXPLOSION SAFETY CATEGORY FOR GAS

None

POTENTIAL ISOLATION

Between Digital inputs 12 V DC and Outputs: yes
Between Analog inputs and Outputs: yes
Between Digital inputs 12 V DC and expansion devices: yes
Between Digital inputs 24 V DC and Outputs: yes
Between Relay outputs and expansion devices: yes
Between Digital inputs 24 V AC and Outputs: yes
Between Relay outputs and Power supply: yes
Between Digital inputs 24 V DC and expansion devices: yes
Between Digital inputs 24 V DC and Ethernet: yes
Basic isolation: 600 V AC (Relay outputs)
Between Analog inputs and expansion devices: yes
Between Relay outputs: yes
Between Relay outputs and Inputs: yes
Between Digital inputs 12 V DC and Ethernet: yes
Between Relay outputs and Ethernet: yes
Safe isolation according to EN 50178: 300 V AC (Relay outputs)
Between Digital inputs 24 V AC and expansion devices: yes
Between Digital inputs 24 V AC and Ethernet: yes

PROTECTION AGAINST POLARITY REVERSAL

Yes, for supply voltage (Siemens MPI optional)

EXPLOSION SAFETY CATEGORY FOR DUST

None

SAFE ISOLATION

300 V AC, Between coil and contact, According to EN 50178
300 V AC, Between two contacts, According to EN

INPUT CURRENT	3.3 mA (I1 - I4, at 24 V DC, at signal 1)
	2.2 mA (I5 - I8, at 24 V DC, at signal 1)
	1 mA (Analog inputs)
	200 mA
INPUT IMPEDANCE	13.3 kΩ
INPUT VOLTAGE	At signal 1: ≥ 15 V (I1 - I8, sinusoidal, Digital inputs, 24 V DC)
	Status 0: ≤ 8 V DC (I5 - I8, Digital inputs, 24 V DC)
	Status 1: ≥ 8 V DC (I5 - I8, Digital inputs, 24 V DC)
	Signal 0: ≤ 5 V DC (I1 - I4, Digital inputs, 12 V DC)
	Status 0: ≤ 15 V DC (I1 - I4, Digital inputs, 24 V DC)
	At signal 0: ≤ 5 V (I1 - I8, sinusoidal, Digital inputs, 24 V DC)
MAKING/BREAKING CAPACITY	28/28 VA (DC, at R 300)
	3600/360 VA (AC, at B 300)
NUMBER OF INPUTS (ANALOG)	0
	4
NUMBER OF INPUTS (DIGITAL)	4
	8
NUMBER OF OUTPUTS (ANALOG)	0
NUMBER OF OUTPUTS (DIGITAL)	4
OUTPUT	4 Relay Outputs
	> 500 mA (Relay outputs, Recommended for load: 12 V AC/DC)
	Relay outputs in groups of 1
	Voltage Current
PARALLEL SWITCHING	Not permitted
RAPID COUNTER INPUTS	10 kHz, Counter frequency
	-2147483648 -
	2147483647 (value range)
	≤ 20 m (cable length, screened)
	1:1 (Pulse pause ratio)
	Square (pulse shape)
	Number: 4 (I1, I2, I3, I4 - Digital inputs 24 V DC)

SIGNAL RANGE	0 - 10 V DC, Analog inputs
---------------------	----------------------------

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4 W
-----------------------------------------------------------	-----

HEAT DISSIPATION CAPACITY PDISS	0 W
----------------------------------------	-----

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
----------------------------------------------------------	-----

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
----------------------------------------------------------------------	-----

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	3 W
-----------------------------------------------------------	-----

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
------------------------------------	--------------------------------------------

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
-----------------------------------------------------------------	--------------------------------------------

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
-----------------------------------------------------------------------------------	--------------------------------------------

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
-----------------------------------------------------------------------------------------	--------------------------------------------

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
---------------------------------------------------------	--------------------------------------------

10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
-----------------------	--------------------------------------------------------------------

10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
---------------------------------	--------------------------------------------------------------------

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
----------------------------	--------------------------------------------

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
------------------------------------------------	--------------------------------------------

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
-----------------------------------------------	--------------------------------------------

10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
-----------------------------------------------	--------------------------------------------------------------------

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

APPLICATION NOTES	eaton-easye4-aws-ap050027-en-us.pdf
BROCHURES	easy E4 control relay-brochure
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-electrical-timers-easy-control-relays-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	DA-DC-00005057.pdf DA-DC-00005048.pdf
DRAWINGS	eaton-modular-plc-starter-kit-dimensions.eps eaton-general-easy-control-relays-symbol-002.tif

	eaton-modular-plc-easy-control-relays-3d-drawing.eps
ECAD MODEL	ETN.EASY-E4-UC-12RC1
INSTALLATION INSTRUCTIONS	IL050020ZU
INSTALLATION VIDEOS	Video easy E4 control relay Control relay easyE4: The new generation
MANUALS AND USER GUIDES	MN050009 EN
MCAD MODEL	DA-CD-uc 12rc1 DA-CS-uc 12rc1
MULTIMEDIA	How to connect the Remote Touch Display EASY-RTD to the easyE4? easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator How to process SmartWire-DT modules using the EASY-COM-SWD-C1 module connected to an easyE4? How to process ModbusRTU devices with the EASY-COM-RTU-M1 module on an easyE4? Handling of the data logger as a ring buffer with the easyE4 using the ST programming language. How to connect the easyE4 to the touch panel XV-102 for easy? - 5 Steps
PRODUCT NOTIFICATIONS	MZ049014EN
SALES NOTES	eaton-control-relay-easye4-flyer-fl050007en-en-us.pdf eaton-easy-remote-touch-display-flyer-fl048004en-en-us.pdf
SOFTWARE, FIRMWARE, AND APPLICATIONS	easyE4 Anwendungsbeispiele e70 KOP EDP

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

