



Contactor, 3 pole, 380 V 400 V 22 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals

Part no. DILM50-EA(230V50HZ,240V60HZ)
190011

General specifications			
Product name			Eaton Moeller® series DILM contactor
Part no.			DILM50-EA(230V50HZ,240V60HZ)
EAN			4015081880072
Product Length/Depth			132.1 millimetre
Product height			115 millimetre
Product width			55 millimetre
Product weight			0.872 kilogram
Compliances			CE Marked RoHS conform CE
Product Tradename			DILM
Product Type			Contactor
Product Sub Type			None
Countries			Turkey Poland Slovakia Romania Czech Republic

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])			
Rated control supply voltage AC 50 Hz	V		230 - 230
Rated control supply voltage AC 60 Hz	V		240 - 240
Rated control supply voltage DC	V		0 - 0
Voltage type for actuating			AC
Number of normally closed contacts as main contact			0
Number of normally open contacts as main contact			3
Type of electrical connection of main circuit			Screw connection
Operating voltage AC 50 Hz	V		230 - 690
Operating voltage AC 60 Hz	V		230 - 690
Rated operation current Ie at AC-1, 400 V	A		80
Rated operation current Ie at AC-3, 400 V	A		50
Rated operation power at AC-3, 400 V	kW		22
Rated operation current Ie at AC-4, 400 V	A		21
Rated operation power at AC-4, 400 V	kW		10
Rated operation power NEMA	kW		29.8
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Modular version			No
Width	mm		55
Height	mm		115
Depth	mm		132.1