

DATASHEET - LZMC2-A160-I



Circuit-breaker, 3 p, 160A

Part no. **LZMC2-A160-I**
111938

General specifications		
Product name		Eaton Moeller series Power Defense molded case circuit-breaker
Part no.		LZMC2-A160-I
EAN		4015081114863
Product Length/Depth		142 millimetre
Product height		185 millimetre
Product width		105 millimetre
Product weight		2.345 kilogram
Compliances		RoHS conform
Certifications		IEC/EN 60947 IEC VDE 0660
Product Tradename		Power Defense
Product Type		Molded case circuit breaker
Product Sub Type		None
Delivery program		
Application		Use in unearthed supply systems at 690 V
Type		Circuit breaker
Circuit breaker frame type		LZM2
Number of poles		Three-pole
Amperage Rating		160 A
Release system		Thermomagnetic release
Features		Protection unit Motor drive optional
Special features		Rated current = rated uninterrupted current: 160 A Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn})
Technical Data - Electrical		
Voltage rating		690 V - 690 V
Rated insulation voltage (U _i)		690 V AC
Rated impulse withstand voltage (U _{imp}) at auxiliary contacts		6000 V
Rated impulse withstand voltage (U _{imp}) at main contacts		8000 V
Rated operational current		300 A (690 V AC-1, making and breaking capacity) 160 A (660-690 V AC-3, making and breaking capacity) 160 A (415 V AC-3, making and breaking capacity) 300 A (380/400 V AC-1, making and breaking capacity) 300 A (415 V AC-1, making and breaking capacity)
Instantaneous current setting (I _i) - min		960 A
Instantaneous current setting (I _i) - max		1600 A
Overload current setting (I _r) - min		125 A
Overload current setting (I _r) - max		160 A
Short delay current setting (I _{sd}) - min		0 A
Short delay current setting (I _{sd}) - max		0 A
Short-circuit release non-delayed setting - min		960 A
Short-circuit release non-delayed setting - max		1600 A
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 230 V, 50/60 Hz		55 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz		36 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 440 V, 50/60 Hz		22.5 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 525 V, 50/60 Hz		6 kA
Rated short-circuit making capacity I _{cm} at 240 V, 50/60 Hz		121 kA
Rated short-circuit making capacity I _{cm} at 400/415 V, 50/60 Hz		76 kA

Rated short-circuit making capacity I _{cm} at 440 V, 50/60 Hz		63 kA
Rated short-circuit making capacity I _{cm} at 525 V, 50/60 Hz		24 kA
Rated short-circuit making capacity I _{cm} at 690 V, 50/60 Hz		14 kA
Short-circuit total breaktime		< 10 ms
Electrical connection type of main circuit		Screw connection
Isolation		300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
Number of operations per hour - max		120
Handle type		Rocker lever
Utilization category		A (IEC/EN 60947-2)
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		7500 operations at 415 V AC-1 7500 operations at 690 V AC-1 6500 operations at 415 V AC-3 10000 operations at 400 V AC-1
Direction of incoming supply		As required
Technical Data - Mechanical		
Mounting Method		Fixed Built-in device fixed built-in technique DIN rail (top hat rail) mounting optional
Degree of protection		In the area of the HMI devices: IP20 (basic protection type) IP20
Degree of protection (IP), front side		IP40 (with insulating surround) IP66 (with door coupling rotary handle)
Degree of protection (terminations)		IP10 (tunnel terminal) IP00 (terminations, phase isolator and band terminal)
Protection against direct contact		Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance		20 g (half-sinusoidal shock 20 ms)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Position of connection for main current circuit		Front side
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Special features		Rated current = rated uninterrupted current: 160 A Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn})
Lifespan, mechanical		20000 operations
Technical Data - Mechanical - Terminals		
Standard terminals		Screw terminal
Terminal capacity (copper busbar)		M8 at rear-side screw connection
Terminal capacity (copper solid conductor/cable)		16 mm ² (1x) at tunnel terminal
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (I _n)		160 A
Equipment heat dissipation, current-dependent		38.4 W
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information			
Functions			System and cable protection