

Specifications



Eaton 197215

Eaton Moeller® series EASY Control relays easyE4 with display (expandable, Ethernet), 100 - 240 V AC, 110 - 220 V DC (cULus: 100 - 110 V DC), Inputs Digital: 8, screw terminal EASY-E4-AC-12RC1

General specifications

PRODUCT NAME	Eaton Moeller® series EASY Control relay
CATALOG NUMBER	197215
EAN	4015081939442
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.25 kg
COMPLIANCES	Eaton supports the product until its end of life EN 61010 IEC/EN 61000-6-2 CULus per UL 61010 IEC/EN 61000-4-2 IEC/EN 61131-2 IEC 60068-2-30 CSA-C22.2 No. 61010 EN 50178 IEC 60664 IEC 60068-2-27 IEC 60068-2-6 IEC/EN 61000-6-3 UL Listed UL Category Control No.: NRAQ, NRAQ7 UL File No.: E205091 DNV GL CE UL hazardous location class I UL hazardous location division 2 UL hazardous location group A (acetylene) UL hazardous location group B (hydrogen) UL hazardous location group C (ethylene) UL hazardous location group D (propane)
CERTIFICATIONS	
CATALOG NOTES	Accuracy of the real-time clock depending on ambient air temperature - fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible
MODEL CODE	EASY-E4-AC-12RC1

Features & Functions	
FEATURES	Networkable (Ethernet) Expandable Display indication of 6 lines x 16 characters
FITTED WITH:	Relay output Timer Keypad Display Real time clock
INDICATION	LCD-display used as status indication of Digital inputs 115/230 V AC

General	
DEGREE OF PROTECTION	IP20
DISPLAY TEMPERATURE - MIN	0 °C
DISPLAY TEMPERATURE - MAX	55 °C
DISPLAY TYPE	Monochrome
INPUT FREQUENCY	50/60 Hz (Digital inputs, at 115/230 V AC) 50/60 Hz (Digital inputs, at 24 V DC)
INSULATION RESISTANCE	According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
LIFESPAN, ELECTRICAL	25,000 Operations (Fluorescent lamp load 1 x 58 W at 230/240 V AC, conventional, compensated) 25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, with upstream electrical device) 25,000 Operations (Filament bulb load at 1000 W, 230/240 V AC) 25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, uncompensated) 25,000 Operations (Filament bulb load at 500 W, 115/120 V AC)
LIFESPAN, MECHANICAL	1,000,000 Operations
MOUNTING METHOD	Screw fixing using fixing brackets ZB4-101-GF1 (accessories) Rail mounting possible Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Wall mounting/direct mounting Front build in possible
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
PRODUCT CATEGORY	Control relays easyE4
PROTECTION	B16 circuit breaker or 8 A (T) fuse, Protection of an Output relay
PROTOCOL	TCP/IP MODBUS
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6 kV (contact-coil)
RESIDUAL RIPPLE	≤ 5 %

RESOLUTION	<ul style="list-style-type: none"> • 1 min (Range H:M) • 1 s (Range M:S) • 5 ms (Range S)
-------------------	--

SOFTWARE	EASYSOFT-SWLIC/easySoft
-----------------	-------------------------

SWITCHING FREQUENCY	10 Hz, Relay outputs 2 Hz, Resistive load/lamp load, Relay outputs 0.5 Hz, Inductive load, Relay outputs
----------------------------	--

TYPE	easyE4 base device
-------------	--------------------

USED WITH	easyE4
------------------	--------

UTILIZATION CATEGORY	B 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes AC R 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes DC
-----------------------------	--

VOLTAGE TYPE	AC
---------------------	----

Ambient conditions, mechanical

DROP AND TOPPLE	50 mm Drop height, Drop to IEC/EN 60068-2-31
------------------------	--

HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	0.3 m
---	-------

MOUNTING POSITION	Horizontal Vertical
--------------------------	------------------------

SHOCK RESISTANCE	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts
-------------------------	---

VIBRATION RESISTANCE	According to IEC/EN 60068-2-6 57 - 150 Hz, 2 g constant acceleration 10 - 57 Hz, 0.15 mm constant amplitude
-----------------------------	---

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
---------------------	----------------------------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
--	-------

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
--	--------

AMBIENT STORAGE TEMPERATURE - MAX	70 °C
--	-------

ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures Clearance in air and creepage distances according to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
---------------------------------	--

RELATIVE HUMIDITY	5 - 95 % (IEC 60068-2-30, IEC 60068-2-78)
--------------------------	---

Electro magnetic compatibility

AIR DISCHARGE	8 kV
----------------------	------

BURST IMPULSE	2 kV, Signal cable According to IEC/EN 61000-4-4 2 kV, Supply cable
----------------------	---

CONTACT DISCHARGE	6 kV
--------------------------	------

ELECTROMAGNETIC FIELDS	3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3)
-------------------------------	--

Terminal capacities

TERMINAL CAPACITY	0.2 - 4 mm ² (AWG 22 - 12), solid 0.2 - 2.5 mm ² (22 - 12 AWG), flexible with ferrule
--------------------------	--

SCREWDRIVER SIZE	3.5 x 0.8 mm, Terminal screw
-------------------------	------------------------------

TIGHTENING TORQUE	0.6 Nm, Screw terminals
--------------------------	-------------------------

	10 V/m at 0.8 - 1.0 GHz (according to IEC EN 61000-4-3)
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class B (EN 61000-6-3)
SURGE RATING	1 kV, Supply cables, symmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5, power pulses (Surge), EMC 2 kV, Supply cables, asymmetrical, power pulses (Surge), EMC
VOLTAGE DIPS	10 ms

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	8 A
INRUSH CURRENT	12.5 A (for 6 ms)
POWER CONSUMPTION	4 W
POWER LOSS	10 W
RATED BREAKING CAPACITY	300000 Operations at AC-15, 250 V AC, 3 A (600 Ops./h) 200000 Operations at DC-13, 24 V DC, 1 A (500 Ops./h)
RATED INSULATION VOLTAGE (UI)	240 V
RATED OPERATIONAL VOLTAGE	Max. 300 V DC 100/110/115/120/230/240 AC (-15 %/+10 %) 85 - 264 V AC Max. 300 V AC 110/120 V DC (power supply) 240 V AC
SUPPLY FREQUENCY	50/60 Hz ($\pm 5\%$)
SUPPLY VOLTAGE AT AC, 50 HZ - MIN	85 VAC
SUPPLY VOLTAGE AT AC, 50 HZ - MAX	264 VAC
SUPPLY VOLTAGE AT DC - MIN	85 VDC
SUPPLY VOLTAGE AT DC - MAX	264 VDC
UNINTERRUPTED CURRENT	5 A AC, max. thermal continuous current $\cos \phi = 1$ at B 300 (UL/CSA) 8 A AC, at 240 V AC (UL/CSA) 8 A DC, at 24 V DC (UL/CSA) 1 A DC, at R 300 (UL/CSA)

Short-circuit rating

SHORT-CIRCUIT PROTECTION	$\geq 1A$ (T), Fuse, Power supply
---------------------------------	-----------------------------------

Communication

CONNECTION TYPE	Screw terminal Ethernet: RJ45 plug, 8-pole
DATA TRANSFER RATE	10/100 MBit/s

Input/Output

ACCURACY	± 1 %, Repetition accuracy of timing relays (of values) ± 2 s/day, Real-time clock to inputs (± 0.2 h/Year)
DELAY TIME	21 ms typ., Digital Inputs 100 - 240 V AC 60 Hz (I1 - I8), Delay time from 0 to 1, Debounce OFF 20 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 0 to 1, Debounce ON 20 ms, Digital inputs 115/230 V AC 50 Hz (I7, I8), Delay time from 1 to 0, Debounce OFF 21 ms typ., Digital Inputs 100 - 240 V AC 60 Hz (I1 - I8), Delay time from 1 to 0, Debounce OFF 16⅔ ms, Digital inputs 115/230 V AC 60 Hz (I7, I8), Delay time from 1 to 0, Debounce OFF 0.03 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 0 to 1, Debounce OFF 0.03 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 1 to 0, Debounce OFF 20 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 1 to 0, Debounce ON
INPUT CURRENT	2 x 4 mA (I7 - I8, at 115 V AC, 60 Hz, at signal 1) 6 x 0.25 mA (I1 - I6, at 115 V AC, 60 Hz, at signal 1) 2 x 6 mA (I7 - I8, at 230 V AC, 50 Hz, at signal 1) 6 x 0.5 mA (I1 - I6, at 230 V AC, 50 Hz, at signal 1)
INPUT VOLTAGE	Condition 0: 0 - 40 V AC, Digital inputs, 115/230 V AC) Condition 1: 79 - 264 V AC, Digital inputs, 115/230 V AC)
MAKING/BREAKING CAPACITY	3600/360 VA (AC, at B 300) 28/28 VA (DC, at R 300)
NUMBER OF INPUTS (ANALOG)	0

Cable

CABLE LENGTH	100 m (max. permissible per input I7 to I8), Digital inputs 115/230 V AC 40 m (max. permissible per input I1 to I6), Digital inputs 115/230 V AC
CABLE TYPE	CAT5

Safety

EXPLOSION SAFETY CATEGORY FOR GAS	None
POTENTIAL ISOLATION	Between Digital inputs 115/230 V AC and Power supply: no Between Relay outputs and expansion devices: yes Between Digital inputs 115/230 V AC: no Between Relay outputs and Inputs: yes Between Digital inputs 115/230 V AC and base unit: yes Between Digital inputs 115/230 V AC and Outputs: yes Between Digital inputs 115/230 V AC and Ethernet: yes Between Relay outputs and Ethernet: yes Basic isolation: 600 V AC (Relay outputs) Between Digital inputs 115/230 V AC and expansion devices: yes Safe isolation according to EN 50178: 300 V AC (Relay outputs) Between Relay outputs: yes Between Digital inputs 115/230 V AC and Memory card: no Between Relay outputs and Power supply: yes Between Digital inputs 115/230 V AC and Interface: yes
PROTECTION AGAINST POLARITY REVERSAL	Yes, for supply voltage (Siemens MPI optional)
EXPLOSION SAFETY CATEGORY FOR DUST	None
SAFE ISOLATION	300 V AC, Between two contacts, According to EN 50178 300 V AC, Between coil and contact, According to EN 50178

NUMBER OF INPUTS (DIGITAL)	8
NUMBER OF OUTPUTS (ANALOG)	0
NUMBER OF OUTPUTS (DIGITAL)	4
OUTPUT	Relay outputs in groups of 1 4 Relay Outputs > 500 mA (Relay outputs, Recommended for load: 12 V AC/DC) Voltage Current
PARALLEL SWITCHING	Not permitted

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	4 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF	Meets the product standard's

Resources

APPLICATION NOTES	eaton-easye4-aws-ap050027-en-us.pdf
BROCHURES	easy E4 control relay-brochure
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-electrical-timers-easy-control-relays-characteristic-curve-002.eps 252U084
DECLARATIONS OF CONFORMITY	DA-DC-00005057.pdf DA-DC-00005048.pdf
DRAWINGS	2723DIM-98 2528DIM-19 eaton-modular-plc-starter-kit-dimensions.eps eaton-logic-relays-easy-control-relays-dimensions-002.eps eaton-modular-plc-easy-control-relays-3d-drawing.eps 2723DRW-420
ECAD MODEL	ETN.EASY-E4-AC-12-RC1
INSTALLATION INSTRUCTIONS	IL050020ZU
INSTALLATION VIDEOS	Control relay easyE4: The new generation Video easy E4 control relay
MANUALS AND USER GUIDES	DA-MN-h1430de MN050009_EN
MCAD MODEL	eaton-cadenas-path-easy_e4-assemblies-uc_12rc1_asmtpl.prj

PROTECTION OF ASSEMBLIES	requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

[eaton-cadenas-front_view-uc_12rc1_front.pra](#)

[eaton-cadenas-side_view-uc_12rc1_side.pra](#)

[DA-CS-uc_12rc1](#)

[DA-CD-uc_12rc1](#)

[Handling of the data logger as a ring buffer with the easyE4 using the ST programming language.](#)

[How to connect the easyE4 to the touch panel XV-102 for easy? - 5 Steps](#)

[How to process SmartWire-DT modules using the EASY-COM-SWD-C1 module connected to an easyE4?](#)

MULTIMEDIA

[How to connect the Remote Touch Display EASY-RTD to the easyE4?](#)

[How to process ModbusRTU devices with the EASY-COM-RTU-M1 module on an easyE4?](#)

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

[MZ049014EN](#)

PRODUCT NOTIFICATIONS

[eaton-easye-product-family-product-cybersecurity-guideline-mz049001en.pdf](#)

[eaton-control-relay-easye4-flyer-fl050007en-en-us.pdf](#)

SALES NOTES

[eaton-easy-remote-touch-display-flyer-fl048004en-en-us.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

