DATASHEET - DILM115-EA(RAC240)



Contactor, 3 pole, 380 V 400 V 55 kW, RAC 240: 190 - 240 V 50/60 Hz, AC operation, Screw terminals

Part no. DILM115-EA(RAC240) 189925

General specifications	
Product name	Eaton Moeller® series DILM contactor
Part no.	DILM115-EA(RAC240)
EAN	4015081879212
Product Length/Depth	160 millimetre
Product height	170 millimetre
Product width	90 millimetre
Product weight	2.25 kilogram
Compliances	CE CE Marked RoHS conform
Product Tradename	DILM
Product Type	Contactor
Product Sub Type	None
Countries	Romania Czech Republic Slovakia Turkey Poland

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC0	000066)			
Electric engineering, automation, process control engineering / Low-voltage switch	technology / Contac	ctor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])		
Rated control supply voltage AC 50 Hz	V	190 - 240		
Rated control supply voltage AC 60 Hz	V	190 - 240		
Rated control supply voltage DC	V	0 - 0		
Voltage type for actuating		AC		
Number of normally closed contacts as main contact		0		
Number of normally open contacts as main contact		3		
Type of electrical connection of main circuit		Screw connection		
Operating voltage AC 50 Hz	V	230 - 690		
Operating voltage AC 60 Hz	V	230 - 690		
Rated operation current le at AC-1, 400 V	Α	160		
Rated operation current le at AC-3, 400 V	А	115		
Rated operation power at AC-3, 400 V	kW	55		
Rated operation current le at AC-4, 400 V	Α	55		
Rated operation power at AC-4, 400 V	kW	28		
Rated operation power NEMA	kW	74		
Number of auxiliary contacts as normally open contact		0		
Number of auxiliary contacts as normally closed contact		0		
Modular version		No		
Width	mm	90		
Height	mm	170		
Depth	mm	160		