



HALT/STOP-Button, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Turn-to-release function, Black, yellow, RAL 9005

Part no. M22S-PVT
271499

General specifications

Product name	Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton
Part no.	M22S-PVT
EAN	4015082714994
Product Length/Depth	38 millimetre
Product height	70 millimetre
Product width	38 millimetre
Product weight	0.045 kilogram
Compliances	CE Marked
Certifications	LR CSA File No.: 012528 UL Category Control No.: NKCR EN 60947-5 DNV CE UL 508 CSA Class No.: 3211-03 UL UL File No.: E29184 CSA Std. C22.2 No. 94-91 VDE IEC/EN 60947-5 CSA IEC 60947-5 GL VDE 0660 CSA Std. C22.2 No. 14-05 IEC/EN 60947 CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91
Product Tradename	M22
Product Type	Emergency stop/emergency switching off pushbutton
Product Sub Type	None

Features & Functions

Bezel color	Other
Base color	Yellow
Bezel material	Other
Color	Black
Design	Classical Mushroom-shaped
Illumination	Non-illuminated
RAL-number	9005
Unlocking method	Turn-release

General information

Degree of protection	NEMA 4X, 13 IP67/IP69K
Lifespan, mechanical	100,000 Operations
Opening diameter	22.5 mm
Operating frequency	600 Operations/h
Product category	RMQ-Titan
Size	Front dimensions: 35 mm
Type	STOP pushbutton Emergency stop pushbutton

Ambient conditions, mechanical

Mounting position	As required
Shock resistance	50 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27

Climatic environmental conditions			
Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C
Climatic proofing			Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Communication			
Connection to SmartWire-DT			With SWD-RMQ connections Yes
Actuator			
Actuating force			50 N
Actuator color			Black
Actuator diameter			38 mm
Actuator function			Turn-to-release Switching function latching
Contacts			
Force for positive opening - min			0 N
Design verification			
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for mushroom push-button (EC001038)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for mushroom push-button actuators (ec@ss13-27-37-12-12 [AKF030019])			
Colour button			Black
Construction type lens			Round
Diameter cap		mm	38
Hole diameter		mm	22.5
Width opening		mm	0
Height opening		mm	0

Degree of protection (IP)			IP67/IP69K
Degree of protection (NEMA)			4X, 13
Type of button			High
Suitable for illumination			No
With lighting			No
Supply voltage lamp		V	0
Switching function latching			Yes
Spring-return			No
With front ring			No
Material front ring			Other
Colour front ring			Other
Suitable for emergency stop			No
Unlocking method			Turn-release