

# Eaton 218145

Catalog Number: 218145

Eaton Moeller® series M22 Double actuator pushbutton, RMQ-Titan, Actuators and indicator lights non-flush, momentary, White lens, black, black, inscribed, Bezel: titanium



### General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller® series M22 Double actuator pushbutton	218145
	<b>EAN</b>
	4015082181451
<b>Model Code</b>	<b>Product Length/Depth</b>
M22-DDL-S-X4/X5	30 mm
<b>Product Height</b>	<b>Product Width</b>
55 mm	30 mm
<b>Product Weight</b>	<b>Certifications</b>
0.015 kg	UL
	UL Category Control No.: NKCR
	VDE 0660
	CSA
	CSA-C22.2 No. 94-91
	CSA-C22.2 No. 14-05
	IEC/EN 60947
	CE
	CSA File No.: 012528
	IEC/EN 60947-5
	UL 508
	UL File No.: E29184
	CSA Class No.: 3211-03
	DNV
	GL
	LR

## Features & Functions

### Bezel color

Titanium

### Bezel material

Plastic

### Design

Non-Flush

Classical

### Features

Labelled

### Fitted with:

Front ring

### Inscription

Inscribed

### Lens color

White

## General

### Degree of protection

NEMA 12

IP66

NEMA 13

NEMA 3R

NEMA 4X

### Degree of protection (front side)

IP66

NEMA 4X

### Lifespan, mechanical

200,000 Operations

### Opening diameter

22.5 mm

### Operating frequency

3600 Operations/h

### Product category

RMQ-Titan

### Size

Front dimensions: 29,7 x 54,7 mm

### Suitable for

Illumination

### Type

Double actuator

## Ambient conditions, mechanical

### Mounting position

As required

### Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27

## Climatic environmental conditions

### Ambient operating temperature - min

-25 °C

### Ambient operating temperature - max

70 °C

### Ambient storage temperature - min

40 °C

### Ambient storage temperature - max

80 °C

### Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

## Communication

Connection to SmartWire-DT

Yes

With SWD-RMQ connections

## Actuator

Actuating force

5 N

Actuator color

Black

Actuator function

Spring-return

Momentary

## Contacts

Force for positive opening - min

0 N

## Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub>

0 W

Heat dissipation capacity P<sub>diss</sub>

0 W

Heat dissipation per pole, current-dependent P<sub>vid</sub>

0 W

Rated operational current for specified heat dissipation (I<sub>n</sub>)

0 A

Static heat dissipation, non-current-dependent P<sub>vs</sub>

0 W

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

Not applicable.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resources

### Catalogs

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

### Certification reports

[0000SPC-183](#)

[0000SPC-179](#)

### Declarations of conformity

[DA-DC-00004135.pdf](#)

[DA-DC-00004157.pdf](#)

### Drawings

[eaton-operating-pushbutton-m22-double-actuator-pushbutton-dimensions-002.eps](#)

[116X107](#)

[116X194](#)

[eaton-operating-pushbutton-m22-double-actuator-pushbutton-dimensions.eps](#)

### Drawings

[eaton-general-approval-m22-symbol.eps](#)

[0000SPC-180](#)

[eaton-general-m22-standards.eps](#)

[1160SPC-30](#)

[eaton-general-m22-symbol.eps](#)

[eaton-operating-button-m22-double-actuator-pushbutton-symbol-008.eps](#)

### eCAD model

[ETN.M22-DDL-S-X4\\_X5](#)

[ETN.218145.edz](#)

### Installation instructions

[IL04716002Z](#)

### Installation videos

[RMQ Flat Design](#)

### mCAD model

[eaton-cadenas-side\\_view-doppeldrucktaste\\_normal\\_normal\\_side.pra](#)

[eaton-cadenas-path-temp-doppeldrucktaste\\_normal\\_normal.3db](#)

[DA-CD-doppeldrucktaste\\_normal\\_normal](#)

[eaton-cadenas-front\\_view-doppeldrucktaste\\_normal\\_normal\\_front.pra](#)

[DA-CS-doppeldrucktaste\\_normal\\_normal](#)

## Multimedia

[MCI MultiColor Light Indicator RMQ compact solution](#)

[MCI Multicolor Light Indicator M22 with SmartWire-DT](#)

[RMQ small E-Stop emergency-stop button](#)

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

## Sales notes

[eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf](#)

## System overview

[Pilot devices - selection aid](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)