DATASHEET - DILM32-XHI31



Auxiliary contact module, 4 pole, Ith= 16 A, 3 N/O, 1 NC, Front fixing, Screw terminals, DILM7-10 - DILM38-10

Part no. DILM32-XHI31

106112

EL Number

4110193

(Norway)

| General specifications | |
|------------------------|--|
| Product name | Eaton Moeller® series DILM auxiliary contact module |
| Part no. | DILM32-XHI31 |
| EAN | 4015081058822 |
| Product Length/Depth | 45 millimetre |
| Product height | 38 millimetre |
| Product width | 36 millimetre |
| Product weight | 0.048 kilogram |
| Certifications | IEC/EN 60947 UL 508 UL Category Control No.: NKCR CE UL CSA-C22.2 No. 14-05 CSA File No.: 012528 IEC/EN 60947-4-1 UL File No.: E29184 CSA CSA C3A C3A C3A C3A C5A C660 |
| Product Tradename | DILM |
| Product Type | Accessory |
| Product Sub Type | Auxiliary contact module |

Technical data ETIM 9.0

| Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041) | | | | |
|--|--|---|------------------|--|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018]) | | | | |
| Number of contacts as change-over contact | | | 0 | |
| Number of contacts as normally open contact | | | 3 | |
| Number of contacts as normally closed contact | | | 1 | |
| Number of fault-signal switches | | | 0 | |
| Rated operation current le at AC-15, 230 V | | Α | 6 | |
| Type of electric connection | | | Screw connection | |
| Model | | | Clip-on | |
| Mounting method | | | Front fastening | |
| Lamp holder | | | None | |