

Specifications

Photo is representative

Eaton 262510

Eaton Moeller® series M22 Accessory Contact element, 1 N/C, 1 N/CL, Front fastening, Cage Clamp, Single contact, Front fixing

General specifications

PRODUCT NAME	Eaton Moeller® series M22 Accessory Contact element
CATALOG NUMBER	262510
EAN	4015082625108
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	32 mm
PRODUCT WEIGHT	0.01 kg
CERTIFICATIONS	CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91 UL Category Control No.: NKCR CSA File No.: 012528 CSA Class No.: 3211-03 IEC/EN 60947-5 UL 508 IEC 60947-5-1 UL File No.: E29184 CE CSA UL
CATALOG NOTES	Contacts with safety function, by positive opening to IEC/EN 60947-5-1
MODEL CODE	M22-CK01D

Features & Functions

ELECTRIC CONNECTION TYPE	Spring clamp connection
---------------------------------	-------------------------

Ambient conditions, mechanical

SHOCK RESISTANCE	30 g, Mechanical, according to IEC/EN 60068-2-27, Shock duration 11 ms
-------------------------	--

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	0.5 - 1.5 mm ²
TERMINAL CAPACITY (SOLID)	0.75 - 2.5 mm ²
TERMINAL CAPACITY (STRANDED)	0.5 - 2.5 mm ²

General

DEGREE OF PROTECTION	IP20
LIFESPAN, ELECTRICAL	1,000,000 Operations (at 230 V, AC-15, 1 A) 700,000 Operations (at 230 V, AC-15, 3 A) 1,200,000 Operations (at 12 V, DC-13, 2.8 A) 1,600,000 Operations (at 230 V, 0.5 A)
LIFESPAN, MECHANICAL	5,000,000 Operations
MODEL	Top mounting
MOUNTING METHOD	Front fastening
OPERATING FREQUENCY	3600 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

RATED INSULATION VOLTAGE (UI)	500 V
RATED OPERATIONAL CURRENT (IE) AT AC-15, 115 V	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	6 A
RATED OPERATIONAL	4 A

CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	
---	--

RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V	2 A
--	-----

RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.6 A
--	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.3 A
---	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	3 A
---	-----

RATED OPERATIONAL CURRENT (IE) AT DC-13, 42 V	1.7 A
---	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	1.2 A
---	-------

Short-circuit rating

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	1 kA
--	------

SHORT-CIRCUIT PROTECTION	PKZM0-10/FAZ-B6/1, Contacts, Max. short- circuit protective device, Fuseless
-----------------------------	---

SHORT-CIRCUIT PROTECTION RATING	Max. 10 A gG/gL, Fuse, Contacts
------------------------------------	------------------------------------

Actuator

ACTUATING FORCE - MAX	5 N
-----------------------	-----

ACTUATOR TRAVEL AND ACTUATION FORCE (DIN EN 60947-5-1)	4.8 mm
--	--------

KNOB TRAVEL	5.7 mm
-------------	--------

Communication

CONNECTION TO SMARTWIRE-DT	No
-------------------------------	----

CONNECTION TYPE	Single contact Front fixing Cage Clamp
-----------------	--

Contacts

CONTROL CIRCUIT RELIABILITY	1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA) 1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)
--------------------------------	--

FORCE FOR POSITIVE OPENING - MIN	15 N
-------------------------------------	------

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
---	---

NUMBER OF CONTACTS (NORMALLY CLOSED)	1
---	---

CONTACTS)

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	0
--	---

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.11 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	6 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.

Resources

	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
CATALOGUES	eaton-rmq-titan-brochure-br047004en-en-us.pdf Flip catalog - Product Range Catalog - Command and indication
CERTIFICATION REPORTS	000Z425
CONTROL TRAVEL DIAGRAM	eaton-operating-diagram-m22-contact-element-contact-travel-diagram.eps
DECLARATIONS OF CONFORMITY	DA-DC-00004975.pdf DA-DC-00004176.pdf DA-DC-00004135.pdf DA-DC-00004157.pdf DA-DC-00004134.pdf DA-DC-00004971.pdf
DRAWINGS	eaton-operating-actuation-m22-led-element-dimensions.eps eaton-operating-contact-m22-contact-element-3d-drawing-004.eps eaton-general-standards-000Z425.jpg eaton-operating-devices-adapter-flow-diagram-003.eps
ECAD MODEL	ETN.262510.edz
FLYERS	eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf
INSTALLATION INSTRUCTIONS	eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf IL04716002Z
INSTALLATION VIDEOS	RMQ Flat Design
MCAD MODEL	kontaktelement_cage_front kontaktelement_cage_front.stp

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

MULTIMEDIA	easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator
	MCI MultiColor Light Indicator RMQ compact solution
	RMQ small E-Stop emergency-stop button
SALES NOTES	MCI Multicolor Light Indicator M22 with SmartWire-DT
	eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf
	eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf
	eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf
	eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf
WIRING DIAGRAMS	eaton-operating-contact-m22-contact-element-wiring-diagram-005.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

