

Specifications

Eaton 197508

Eaton Moeller® series EASY easyE4 control relay, basic unit with display (expandable, Ethernet), 100–240 VAC, 100–240 VDC (cULus: 100–110 VDC), digital inputs: 8, digital outputs: 4 relay, push-in

General specifications

PRODUCT NAME	Eaton Moeller® series EASY Control relay
CATALOG NUMBER	197508
EAN	4015081940868
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.25 kg
COMPLIANCES	Eaton supports the product until its end of life
CERTIFICATIONS	IEC/EN 61000-4-2 EN 55011 EN 55022 IEC 60068-2-6 IEC/EN 61000-4 IEC 60068-2-27 UL Listed UL Category Control No.: NRAQ, NRAQ7 IEC/EN 61131-2 IEC 60068-2-30 EN 61010 IEC/EN 61000-6-3 IEC/EN 61000-6-2 EN 50178 UL File No.: E205091 DNV GL CE UL hazardous location class I UL hazardous location division 2 UL hazardous location group A (acetylene)



Powering Business Worldwide

Features & Functions

FEATURES

Expandable
Networkable (Ethernet)

FITTED WITH:

Relay output
Timer
Keypad
Real time clock

INDICATION

LCD-display used as status
indication of Digital inputs
115/230 V AC

UL hazardous location
group B (hydrogen)
UL hazardous location
group C (ethylene)
UL hazardous location
group D (propane)

CATALOG NOTES

Accuracy of the real-time
clock depending on
ambient air temperature -
fluctuations of up to ± 5
s/day (± 0.5 h/year) are
possible

MODEL CODE

EASY-E4-AC-12RC1P

General

DEGREE OF PROTECTION

IP20

DISPLAY TYPE

Monochrome

INPUT FREQUENCY

50/60 Hz (Digital inputs, at
115/230 V AC)
50/60 Hz (Digital inputs, at
24 V DC)

INSULATION RESISTANCE

According to EN 50178, EN
61010-2-201, UL61010-2-
201, CSA-C22.2 NO. 61010-
2-201

LIFESPAN, ELECTRICAL

25,000 Operations
(Fluorescent lamp load 1 x
58 W at 230/240 V AC,
conventional,
compensated)
25,000 Operations
(Fluorescent lamp load 10
x 58 W at 230/240 V AC,
with upstream electrical
device)
25,000 Operations
(Fluorescent lamp load 10
x 58 W at 230/240 V AC,
uncompensated)
25,000 Operations
(Filament bulb load at 500
W, 115/120 V AC)
25,000 Operations
(Filament bulb load at
1000 W, 230/240 V AC)

LIFESPAN, MECHANICAL

1,000,000 Operations

MOUNTING METHOD

Top-hat rail fixing
(according to IEC/EN
60715, 35 mm)
Screw fixing using fixing
brackets ZB4-101-GF1

	(accessories) Front build in possible Rail mounting possible
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
PRODUCT CATEGORY	Control relays easyE4
PROTECTION	B16 circuit breaker or 8 A (T) fuse, Protection of an Output relay
PROTOCOL	MODBUS TCP/IP
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6 kV (contact-coil)
RESIDUAL RIPPLE	5 % (transistor outputs) ≤ 5 %
RESOLUTION	<ul style="list-style-type: none"> • 1 min (Range H:M) • 1 s (Range M:S) • 5 ms (Range S)
SOFTWARE	EASYSOFT-SWLIC/easySoft
SWITCHING FREQUENCY	0.5 Hz, Inductive load, Relay outputs 10 Hz, Relay outputs 2 Hz, Resistive load/lamp load, Relay outputs
TYPE	easyE4 base device
USED WITH	easyE4
UTILIZATION CATEGORY	B 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes AC R 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes DC
VOLTAGE TYPE	AC

Ambient conditions, mechanical

DROP AND TOPPLE	50 mm Drop height, Drop to IEC/EN 60068-2-31
HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	0.3 m
MOUNTING POSITION	Vertical Horizontal
SHOCK RESISTANCE	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	10 - 57 Hz, 0.15 mm constant amplitude According to IEC/EN 60068-2-6 57 - 150 Hz, 2 g constant acceleration

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures Clearance in air and creepage distances according to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
RELATIVE HUMIDITY	5 - 95 % (IEC 60068-2-30, IEC 60068-2-78)

Electro magnetic compatibility

AIR DISCHARGE	8 kV
BURST IMPULSE	2 kV, Signal cable 2 kV, Supply cable According to IEC/EN 61000-4-4
CONTACT DISCHARGE	6 kV
ELECTROMAGNETIC FIELDS	1 V/m at 2 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 0.08 - 1.0 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
IMMUNITY TO LINE- CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class B (EN 61000-6-3)
SURGE RATING	1 kV, Supply cables, symmetrical, power pulses (Surge), EMC 2 kV, Supply cables, asymmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5 Level 4
VOLTAGE DIPS	10 ms

Terminal capacities

TERMINAL CAPACITY	0.2 - 4 mm ² (AWG 22 - 12), solid 0.2 - 2.5 mm ² (22 - 12 AWG), flexible with ferrule
--------------------------	--

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	8 A
POWER CONSUMPTION	4 W
POWER LOSS	10 W
RATED BREAKING CAPACITY	200000 Operations at DC-13, 24 V DC, 1 A (500 Ops./h) 300000 Operations at AC-15, 250 V AC, 3 A (600 Ops./h)
RATED INSULATION VOLTAGE (UI)	240 V
RATED OPERATIONAL VOLTAGE	Max. 300 V AC Max. 300 V DC 85 - 264 V AC 100/110/115/120/230/240 AC (-15 %/+10 %)
SUPPLY FREQUENCY	50/60 Hz (± 5%)
SUPPLY VOLTAGE AT AC, 50 HZ - MIN	85 VAC
SUPPLY VOLTAGE AT AC, 50 HZ - MAX	264 VAC
SUPPLY VOLTAGE AT DC - MIN	85 VDC
SUPPLY VOLTAGE AT DC - MAX	264 VDC
UNINTERRUPTED CURRENT	1 A DC, at R 300 (UL/CSA) 10 A AC, at 240 V AC (UL/CSA) 8 A DC, at 24 V DC (UL/CSA) 5 A AC, max. thermal continuous current $\cos \phi = 1$ at B 300 (UL/CSA)

Communication

CONNECTION TYPE	Ethernet: RJ45 plug, 8-pole Push in terminals
DATA TRANSFER RATE	10/100 MBit/s

Short-circuit rating

SHORT-CIRCUIT PROTECTION	≥ 1A (T), Fuse, Power supply
---------------------------------	------------------------------

Cable

CABLE LENGTH	100 m (max. permissible per input I7 to I8), Digital inputs 115/230 V AC 40 m (max. permissible per input I1 to I6), Digital inputs 115/230 V AC
CABLE TYPE	CAT5

Input/Output

ACCURACY	± 2 s/day, Real-time clock to inputs (± 0.2 hYear) ± 1 %, Repetition accuracy of timing relays (of values)
-----------------	---

DELAY TIME	21 ms typ., Digital Inputs 100 - 240 V AC 60 Hz (I1 - I8), Delay time from 1 to 0, Debounce OFF 16⅔ ms, Digital inputs 115/230 V AC 60 Hz (I7, I8), Delay time from 1 to 0, Debounce OFF 0.03 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 0 to 1, Debounce OFF 0.03 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 1 to 0, Debounce OFF
-------------------	---

DELAY TIME	20 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 1 to 0, Debounce ON 21 ms typ., Digital Inputs 100 - 240 V AC 60 Hz (I1 - I8), Delay time from 0 to 1, Debounce OFF 20 ms typ., Digital Inputs 100 - 240 V DC (I1 - I8), Delay time from 0 to 1, Debounce ON 20 ms, Digital inputs 115/230 V AC 50 Hz (I7, I8), Delay time from 1 to 0, Debounce OFF
-------------------	--

INPUT CURRENT	2 x 6 mA (I7 - I8, at 230 V AC, 50 Hz, at signal 1) 2 x 4 mA (I7 - I8, at 115 V AC, 60 Hz, at signal 1) 6 x 0.25 mA (I1 - I8, at 115 V AC, 60 Hz, at signal 1)
----------------------	--

INPUT VOLTAGE	Condition 1: 79 - 264 V AC, Digital inputs, 115/230 V AC) Condition 0: 0 - 40 V AC, Digital inputs, 115/230 V AC)
----------------------	--

MAKING/BREAKING CAPACITY	28/28 VA (DC, at R 300) 3600/360 VA (AC, at B 300)
---------------------------------	---

NUMBER OF INPUTS (ANALOG)	0
----------------------------------	---

Safety

EXPLOSION SAFETY CATEGORY FOR GAS	None
--	------

POTENTIAL ISOLATION	Basic isolation: 600 V AC (Relay outputs) Between Analog inputs and Digital inputs: no Between Relay outputs: yes Between Digital inputs 115/230 V AC and Interface: yes Between Digital inputs 115/230 V AC and Memory card: no
----------------------------	--

PROTECTION AGAINST POLARITY REVERSAL	Yes
---	-----

EXPLOSION SAFETY CATEGORY FOR DUST	None
---	------

SAFE ISOLATION	300 V AC, Between coil and contact, According to EN 50178 300 V AC, Between two contacts, According to EN 50178
-----------------------	--

NUMBER OF INPUTS (DIGITAL)	8
NUMBER OF OUTPUTS (ANALOG)	0
NUMBER OF OUTPUTS (DIGITAL)	4
OUTPUT	Voltage Relay outputs in groups of 1 > 500 mA (Relay outputs, Recommended for load: 12 V AC/DC) Current 4 Relay Outputs
PARALLEL SWITCHING	Not permitted

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	4 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Resources

APPLICATION NOTES	eaton-easye4-aws-ap050027-en-us.pdf
BROCHURES	easy E4 control relay-brochure
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-electrical-timers-easy-control-relays-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	DA-DC-00005048.pdf DA-DC-00005057.pdf
DRAWINGS	eaton-modular-plc-starter-kit-dimensions.eps eaton-modular-plc-easy-control-relays-3d-drawing.eps
ECAD MODEL	DA-CE-ETN.EASY-E4-AC-12-RC1P
INSTALLATION INSTRUCTIONS	IL050020ZU
INSTALLATION VIDEOS	Control relay easyE4: The new generation Video easy E4 control relay
MANUALS AND USER GUIDES	MN050009_EN
MCAD MODEL	DA-CS-uc 12rc1 DA-CD-uc 12rc1
MULTIMEDIA	How to process ModbusRTU devices with the EASY-COM-RTU-M1 module on an easyE4? How to process SmartWire-DT modules using the EASY-COM-SWD-C1 module connected to an easyE4? easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

	Handling of the data logger as a ring buffer with the easyE4 using the ST programming language. How to connect the easyE4 to the touch panel XV-102 for easy? - 5 Steps How to connect the Remote Touch Display EASY-RTD to the easyE4?
PRODUCT NOTIFICATIONS	MZ049014EN
SALES NOTES	eaton-easy-remote-touch-display-flyer-fl048004en-en-us.pdf eaton-control-relay-easye4-flyer-fl050007en-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

