

DATASHEET - DILM7-01-EA(230V50HZ,240V60HZ)



Contactor, 3 pole, 380 V 400 V 3 kW, 1 NC, 230 V 50 Hz, 240 V 60 Hz, AC operation, Screw terminals

**Part no. DILM7-01-EA(230V50HZ,240V60HZ)
190027**

General specifications		
Product name		Eaton Moeller® series DILM contactor
Part no.		DILM7-01-EA(230V50HZ,240V60HZ)
EAN		4015081880232
Product Length/Depth		75 millimetre
Product height		68 millimetre
Product width		45 millimetre
Product weight		0.24 kilogram
Compliances		CE CE Marked RoHS conform
Product Tradename		DILM
Product Type		Contactor
Product Sub Type		None
Countries		Turkey Romania Slovakia Poland Czech Republic

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])			
Rated control supply voltage AC 50 Hz	V		230 - 230
Rated control supply voltage AC 60 Hz	V		240 - 240
Rated control supply voltage DC	V		0 - 0
Voltage type for actuating			AC
Number of normally closed contacts as main contact			0
Number of normally open contacts as main contact			3
Type of electrical connection of main circuit			Screw connection
Operating voltage AC 50 Hz	V		24 - 690
Operating voltage AC 60 Hz	V		24 - 690
Rated operation current Ie at AC-1, 400 V	A		22
Rated operation current Ie at AC-3, 400 V	A		7
Rated operation power at AC-3, 400 V	kW		3
Rated operation current Ie at AC-4, 400 V	A		5
Rated operation power at AC-4, 400 V	kW		2.2
Rated operation power NEMA	kW		2.2
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			1
Modular version			No
Width	mm		45
Height	mm		68
Depth	mm		75